

Paper Inkjet Gloss D01

TOP FACE

Caliper	ca. 101 μm +/- 10%
Grammage	ca. 87 g/m^2 +/- 10%

BACKING

Caliper	ca. 55 μm +/- 10%
Grammage	ca. 62 g/m^2 +/- 10%
Remarks	Siliconised Glassine White

ADHESIVE

Type of adhesive	Acrylic water based adhesive.
Properties and applications	Designed to give high tack and adhesion to polar substrates. The adhesive has been Isega approved for direct contact with dry, moist and non-fatty foods .
Temperature range	-40°C to +80°C
Labeling temperature	min. +5 °C
Loop tack	13 to glass (N/25mm), according FINAT 9

OTHERS

Printability	This grade is used mainly for commercial inkjet printing, it is universally printable with pigmented and dye based inks. We recommend checking the suitability of this product on your individual printer before use. To ensure a smudge free print and to maximize water resistance, print with reduced ink saturation.
Storage	After printing the remaining roll must be removed and stored in a cool, clean and dry environment. Keep the material in the original packaging when not used in order to protect it from dust and contamination. Do not expose to direct sunlight or heat sources. Shelf life, up to 12 months.
Disposal	The left-over pieces of film can be treated as industrial waste and incinerated. Nevertheless, it is absolutely necessary to follow the local regulations in force in the waste treatments plants.
Remarks	The above technical information, statements and recommendations are based upon tests believed to be reliable but do not constitute a guarantee or warranty.